

New Product Alert



Belt Curve Conveyor

KGF-P 2040

Volume 11, April 2007

- [mk Web](#)
- [About Us](#)
- [E-mail us](#)

System KGF-P 2040, the latest addition to our conveyor line, is compatible with all other mk conveyor systems. This conveyor features a standard 20 mm rolling knife edge which allows for the transfer of small parts. Automatic belt tensioning is built in and compensates for normal belt stretch, while ensuring a fixed, unchanging installed dimension.

The conveyor belt is entirely supported by a stainless steel slider bed thus providing low friction and product support along its entire running surface. The use of our structural 40x40 mm aluminum extrusion ensures rigid construction with excellent load bearing capacities. The frame features 10mm T-Slots which allow for the direct mounting of side rails, sensors and other accessories.

[Download
PDF Brochure](#)

Features

- Low belt wear
- Automatic belt tensioning
- Quick belt change
- Drive below conveyor—no interference
- Maintenance friendly

Contact

mk Automation, Inc. ▪ 105 Highland Park Drive ▪ Bloomfield, CT 06002
 Phone: 860.769.5500 ▪ Fax: 860.769.5505
 e-mail: sales@mkprofiles.com
 Web: www.mkprofiles.com



Technical Information	
Radius	90, 180 Deg.
Widths	300, 400, 500, 600 mm
Drive location	Below, center, bi-directional
Speed	5 to 80 m/min
Max. Load	50 kg
Belt	various options available